



NUTRI-PLACER

930 & 940 PULL-TYPE APPLICATOR
HCS CHISEL SHANK
SPECIFICATIONS



NUTRI-PLACER 930 & 940 PULL-TYPE APPLICATOR HCS CHISEL SHANK SPECIFICATIONS

FEATURES

- HCS (High Clearance Shank) mount
- 1¼" x 2" edge-bent chisel shank
- Auto-reset design
- Holding force adjustable to either 850 lbs. or 1250 lbs.
- Accepts front mount style knives
- Wide range of working widths available
- Commercial quality frames
- Transport dimensions provide excellent roading capabilities
- High, under frame clearance for residue flow
- Hydraulic single-point depth control
- Constant level rear hitch for simple, reliable hook-up



NUTRI-PLACER	930 SERIES					940 SERIES		
	27.5 FT. (8.4 M)	32.5 FT. (9.9 M)	37.5 FT. (11.4 M)	42.5 FT. (13 M)	47.5 FT. (14.5 M)	50 FT. (15.2 M)	60 FT. (18.3 M)	65 FT. (19.8 M)
Frame Style	Pull-type							
Shank Assembly	HCS mount with 1 ¼" x 2" edge bent chisel shank for front mount knife							
Row Spacing	15 in. (938 cm) or 30 in. (76 cm)							
HCS Chisel Shank Configuration	21 Shanks on 15" 11 Shanks on 30"	25 Shanks on 15" 13 Shanks on 30"	29 Shanks on 15" 15 Shanks on 30"	33 Shanks on 15" 17 Shanks on 30"	37 Shanks on 15" 19 Shanks on 30"	39 Shanks on 15" 20 Shanks on 30"	47 Shanks on 15" 24 Shanks on 30"	51 Shanks on 15" 26 Shanks on 30"
Configuration	3 Section fold, 3 section flex			5 Section fold, 3 section flex		5 Section fold, 3 section flex	7 Section fold, 5 section flex	
Transport Height	10 ft. 6 in. (3.2 m)	12 ft. 4 in. (3.7 m)	13 ft. 10 in. (4.2 m)	13 ft. 6 in. (4.1 m)		13 ft. 9 in. (4.2 m)		
Transport Width	16 ft. 10 in. (5.1 m)			18 ft. 6 in. (5.6 m)		18 ft. 9 in. (5.7 m)		
Main Transport Wheels	Walking tandems Qty 4 – 11L x 15 stubble resistant FI tires with 8-bolt hubs				Walking tandem Qty 4 – 12.5L x 15 stubble-resistant FI tires with 8-bolt hubs		Walking tandem 4 x 16.5 – 16.1 14 ply (Optional stubble-resistant FI tires with 8-bolt hubs)	
Wing Wheels	Walking tandems Qty 4 – 9.5L x 15 stubble resistant FI tires with 6-bolt hubs				Walking tandem Qty 4 – 9.5L x 15 stubble-resistant FI tires with 6-bolt hubs		Walking tandem 8 x 12.5L – 15 10 ply (Optional stubble-resistant FI tires with 6-bolt hubs)	
Outer Gauge Wheel	None				Pin adjust Qty 2 – 9.5L x 15 stubble-resistant FI tires		None Pin adjust 2 x 20.5 – 8 load range D	
Rear Hitch	Optional constant level rear hitch 25,000 lbs (11,340 kg) towing capacity							
HP Requirement	170 – 275 Engine HP	200 – 325 Engine HP	230 – 375 Engine HP	260 – 425 Engine HP	290 – 475 Engine HP	315 – 500 Engine HP	375 – 600 Engine HP	405 – 650 Engine HP

SAFETY NEVER HURTS![™] Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2016 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH12171501

