

TD65-2B Tri-Deck Finishing Mower

In a Class of Its Own

The Progressive **TD65-2B** is designed to maintain large mowing areas. Using your own tractor, the **TD65-2B** is capable of mowing over 60 acres in an 8 hour day at speeds up to 6 miles per hour. Three independent floating mower decks mounted on a transport frame follow the ground conditions found in school yards, recreation areas, and golf courses, to produce a superlative after cut appearance.

Our superior quality of cut is produced by virtue of high lift blades producing enough vacuum to lift grass for an even cut and then dispersing it evenly. The mowing decks unique design also assists in the even dispersion of clippings through the open rear discharge area.

Only minutes are required to change the cutting height from 1" to 5" without the use of tools. All transport and mowing functions are activated without leaving the tractor seat. Maintenace Free Blade Spindles offer peace of mind and lower cost of operation.

If a large area mower purchase is in your plans, consider the **TD65-2B's** rugged construction, functional design, low maintenance requirements and very competitive price.

The **TD65-2B** is another example of the ingenuity and quality that goes into producing a durable, reliable rotary finishing mower that is easy to maintain. The **TD65-2B** is not only in a Class of its Own, it is "**The Better Built Choice**".





TD65-2B Tri-Deck Finishing Mower

Features and Benefits

Overall hook-up made easy:

Often mowers of this size are moved between tractors that are equipped with different size tires or used with different attachments. Realizing this, Progressive offers the TD65-2B with a constant velocity (CV) input PTO as standard equipment, making connection to a tractor easier. - Let's go mowing!



Maintenance Free Blade Spindles are used to both lower cost and time of routine maintenace. They also provide peace of mind that a missed greasing won't render the mower out of service. Mechanical locks secure the decks in the transport position. Optional transport tires and fenders are available if the mower needs to be towed longer distances. All pivot points are fitted with easy to reach grease fittings making servicing fast and easy. A single piece 3/16" steel deck is formed and welded with bracing at high stress areas to provide for maximum structural strength.



The **TD65-2B** is easy on the turf. Low ground pressure is achieved with 12 large low pressure floatation tires. Tire position is staggered to minimize soil compaction and rutting. Six non-swiveling caster tires as well as the two main transport tires keep mower tracking straight while mowing along hillsides.

A superior cut for a superior finish:

High lift rotary blades create enough vacuum to lift the grass for a clean even cut and then disperse the clippings evenly through the rear of each deck for a superior after cut appearance. An optional mulching kit is available to help return clipping nutrients to the soil.







TD65-2B Tri-Deck Finishing Mower Specifications

Part Number: TD65-2B 526512B Recommended PTO HP: 25-40 12 feet 2.380 lbs Cutting width: Weight: Mowing Capacity*: Transport Width: 7.5 feet 2 mph 2.9 acres / hour Transport Height: 4 mph 5.8 acres / hour 5.5 feet 6 mph 8.7 acres / hour Transport Length: 14 feet

Turning Radius: 24" uncut circle

Transport Tires: Two 18 X 9.50 X 8 NHS, 6 ply, Turf Saver Tires (standard)

*Assumes no overlap or turning

Under our policy of continuous improvement, we reserve the right to change specifications and designs without prior notice. The illustrations shown do not necessarily represent the standard version of product offered by Progressive Turf Equipment Inc.

(800) 668-8873 (519) 527-1080 FAX: (519) 527 2275 www.progressiveturfequip.com info@progressiveturfequip.com